



DRAWINGS FOR ILLUSTRATIVE PURPOSES ONLY

Wire (Carbon Steel):

Cold-drawn steel wire conforming to ASTM A 82:

Tensile Strength - 80,000 p.s.i.

Yield Point - 70,000 p.s.i. minimum

Zinc Coating:

Hot-dip galvanized after fabrication: ASTM A 153 (1.5 oz/ft²)

NOTE: Blok-Lok will certify to a minimum of 2.0 oz/ft²

Wire (Stainless Steel):

ASTM A 580 - AISI Type 304 (Type 316 available on special order)

Sheet Metal (Carbon Steel):

ASTM A 366

Zinc Coating:

ASTM A 153 Class B (sheet metal ties and anchors hot-dip galvanized after fabrication).

NOTE: Blok-Lok will certify to a minimum of 2.0 oz/ft²

Sheet Metal (Stainless Steel):

ASTM A 666, ASTM A 480, ASTM A 240, ASTM A 167 - AISI Type 304 Stainless Steel (sheet metal ties and anchors) (Type 316 available on special order).

NOTE: Blok-Lok recommends Stainless Steel for maximum protection against corrosion.

SEISMIC NOTCH ANCHOR:

Thickness:

16 gauge

Length:

3"

4"

5"

Finish:

Hot-Dip Galvanized

Stainless Steel

CONTINUOUS WIRE:

Thickness:

9 gauge

3/16"Ø

CONTINUOUS CHANNEL:

Thickness:

22 gauge

Holes spaced 12" O.C., 10' length, 5/7" profile

Finish:

Hot-Dip Galvanized

Stainless Steel